

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 04-162644

(43)Date of publication of application : 08.06.1992

(51)Int.Cl.

H01L 21/66

(21)Application number : 02-287049

(71)Applicant : HITACHI LTD

HITACHI TOKYO ELECTRON CO LTD

(22)Date of filing : 26.10.1990

(72)Inventor : KAGEYAMA JOICHIRO



ITO TSUTOMU

(54) IDENTIFICATION OF SEMICONDUCTOR WAFER AND SEMICONDUCTOR DEVICE

(57)Abstract:

PURPOSE: To facilitate the recognition of good and bad articles based upon characteristic retrieval results of semiconductor device by applying a badness identification figure comprising a plurality of points to a bad semiconductor device based upon the characteristic inspection result for each semiconductor device.

CONSTITUTION: Characteristics of a plurality of semiconductor devices 3 are inspected. A failure identifying symbol 5 is formed on a failure semiconductor device 3B based upon the result of the inspection. The failure identifying symbol 5 is formed with a plurality of points 7. A semiconductor wafer is cut down for each semiconductor pellet 3. The failure identifying symbol 5 of a semiconductor pellet 3 cut manually or through a proper device is recognized. For example, with use of an optical sensor the failure identifying symbol 5 is constructed into an L shape, and a pattern of the semiconductor device 3, any damage and any contamination of a mirror surface part of a peripheral part of the semiconductor wafer 1 are distinctly discriminated. Based upon the recognition of the failure identifying symbol 5 only good semiconductor devices 3 are extracted.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the
examiner's decision of rejection or application
converted registration]